


SCG Concrete Roof Tile Prestige Series

SCG Concrete Roof Tiles Prestige Series

Natural feeling flat roof tiles that offer the best relaxing time with elegant designs that fit all housing styles and reflect your uniqueness

Flat roof tiles in 2 designs and 2 color groups with natural texture and various color tones that match all housing styles, making your house uniquely beautiful. Feel relaxed with the new type of leisure that you will love.





"Outstanding multi-level roofing house...unique beauty under simply attractive Prestige roof"



Prempracha Group Amphoe Bang Pa-in, Ayutthaya Province Prestige

Honey Brown color



"Simplicity of living decorated with freedom of color from nature with Prestige roof offering a relaxing feeling"



Prempracha Group Amphoe Bang Pa-in, Ayutthaya Province Prestige Log Brown color



"With natural style house decoration that perfectly matches with Prestige roof, the house is harmoniously beautiful under the atmosphere surrounded by mountains"



Khun Prasert Sukokattanachai Amphoe Pak Chong, Nakom Ratchasima

Province

Prestige Tropical Green color




"Beautiful house with serenity surrounded by trees together with the beauty of Prestige roof that offers naturally relaxing feeling"



Khun Jatura Poungthammasakul Amphoe Pak Chong,


Nakorn Ratchasima Province Prestige Tropical Green color

Convenient...with Full Benefits For Perfectly Beautiful Roof



SCG transparent roof for Prestige concrete roof

Light brown 50-60% transparent roof suitable for a corner that needs natural light, saving on electricity costs. The light passing into the building can also better reduce dampness.



Transparent roof tile



SCG pipe vent tile set and pipe vent ridge set for Prestige concrete roof

Designed to meet the requirement for installing other Prestige concrete roof accessories, e.g. TV antenna, air vent pipe, smokestack, lightning rod, pipe for solar water heater, or other pipe that is required to pass t hrough the roof without punching the tiles. Convenient to install for beautiful, neat, and leak-proof work.



Pipe vent tile set




SCG Prestige pipe vent ridge set



SCG wall fitting system for Prestige concrete roof

Prestige wall ridge and wall verge designed to match with Prestige roof tile for perfectly beautiful roof that is leak-proof with leak-prevention abutment fixing set.





SCG eave filling unit for Prestige concrete roof

Preventing small animals from causing damage under the roof and reducing dampness under the roof with air vent. Quick, convenient and easy to install.



Eave filler unit

SCG ROOF SERVICE

(Roof installation service by SCG)

Total roof installation service that is convenient, all-inclusive, value for money, and reliable with SCG standard of expertise and superior capabilities





Beautiful and elegant roof

With expert-level standard control system throughout the process



Confident and worry-free With quality guarantee




Safe for life and property

With cutting-edge devices and advanced security system



Budget and sohedule control With total control management system

SCG Concrete Roof Tiles Prestige Series and Fittings



Product Specifications (Approximate): Other Specifications

Tile size	33x42	cm
Minimum roof slope	25	degrees
Maximum roof slope	40	degrees
Recommended roof slope	35-40	degrees
Length of purlin	31-33	cm
Number of tiles used	10-11	tiles/m²

Tile Weight (Approximate):

Tile weight	5.2	kg/tile
Constant weight used in roof	55	kg/m²
Structure design (Dead Load)		

Tile Fixing Standard:

Fixing with at least two 2-inch screws per purlin for all tiles and rows

(Fixing method is in accordance with the company's standard)

- · SCG concrete roof tile Prestige series is designed for using in Thailand's tropical climate and it passed the wind-rain simulation test according to Thailand's meteorological data through the wind tunnel test in England in accordance with Wind Tunnel Procedure of British Standard BS6567.
- · SCG concrete roof tile Prestige series is high quality roof tiles produced by advanced technology and Wet on Wet color coating system using inorganic pigments to ensure a perfect blend with the tiles and long-lasting color for the entire useful life of the tiles.
- · Wall fitting set is specially designed to match with the tile's characteristics and suitable for any spot that requires fittings.

Installation

Install fittings with advanced Dry Tech System and fix fittings with Mechanical Fixing without mortar. The roof will have no cement stains and the fittings will not be loosened from strong wind. The job is of higher standard without depending on a contractor's expertise. Importantly, this method prevents leaks.

▲ Instructions for safe use of SCG concrete roof tile Prestige series

- 1. Please refer to and follow the installation manual strictly before starting roof installation
- en updated regularly. The product buyer/user, designer, construction controller, and installer shall check whether the manual used is the latest version.

 n, please check at www.scgbuildingmaterials.com or SCG Contact Center 02-586-2222.
- Concrete roof tiles and fittings are designed for pitched roof (pitched roof means roof with a constant dihedral angle without curves, e.g. gable roof, hip roof, or mixed gable and hip roof) with
 a certain dihedral angle as specified for each type of roof according to "installation manual" only.
 Tile surface is slippery and sloping. Do not go up on the roof unnecessarily. If necessary, it shall be done by an expert only.

- Do not go up on the roof when the tiles are wet or moist as you might slip and fall from the roof
 When moving and storing roof tiles, please strictly follow loading, transport and storing standard manual
 Do not use foam-type heat insulation sprayed under the roof as it might affect the roof performance later g standard manual specified by the company to prevent hazard that might occur during work.

MHB-S-R21-C001-6101 • This ve



All Content, design and layout are Copyright © 2018, SCG Cement-Building Materials All Rights Reserved, Reproduction in whole or part in any fo









Email: contact@scg.com, www.scgbuildingmaterials.com